



# Boarding and Sarking



## A comprehensive range.

We offer a comprehensive range of boarding sizes and specifications; all packaged to length and pinned every second row to aid drying.

Suitable for use in a variety of applications including:

- Sarking (roofing boards)
- Packing cases
- Pallet boards
- Fencing slats, gravel & ranch boards

Automated, in-line x-cutting facilities at each of our mills mean that we can process x-cut to length boards quickly and efficiently.

- FSC mixed 70% TT-COC-1503
- Comprehensive specification range
- Heat Treatment (ISPM 15 56/30)
- Kiln Drying
- Combined Kiln Drying & Heat Treatment (ISPM 15 56/30)
- Preservative treatment – Tanalith® "E" / Osmose® AC500 (To the appropriate use classifications)
- Anti-sap stain treatment (Anti Blu)





## Boarding

mm	Aboyne	Mosstodloch	Lockerbie I	Lockerbie III
16 x 75	✓	✓	✓	✓
16 x 100/95	✓	✓	✓	✓
16 x 150	✓	✓	✓	✓
19 x 75	✓	✓		✓
19 x 100	✓	✓		✓
19 x 150	✓	✓		✓
22 x 75	✓	✓		✓
22 x 100	✓	✓	✓	✓
22 x 150	✓	✓		✓

mm	2.4	3	3.6	4.2	4.8	5.4
16 x 75	✓	✓	✓	✓	✓	
16 x 95/100	✓	✓	✓	✓	✓	
19 x 75	✓	✓	✓	✓	✓	✓
19 x 100	✓	✓	✓	✓	✓	✓
19 x 150	✓	✓	✓	✓	✓	✓
22 x 75	✓	✓	✓	✓	✓	
22 x 100	✓	✓	✓	✓	✓	
22 x 150	✓	✓	✓	✓	✓	

Lengths & specifications out-with this list may also be available – please enquire.