

James Jones has built a solid reputation for quality timber products throughout its long trading history. Our **INC15ED** range of products add to this reputation.

INCISING technology is an established and proven process with a history of performance in North America. James Jones was the first timber processor in the UK to adopt this system.

James Jones use market leading wood preservatives from Arch Timber Protection and Wolman within our timber treatment facilities to produce our high performance treated timbers.



Incisions along the entire length of our components create a neat yet distinctive pattern on all 4 sides. This allows the subsequent preservative treatment, applied under pressure, to penetrate deeper into the structure of the timber creating a robust and uniform envelope of protection.

We believe our **INC15ED** Use Class 4 treatment, as recommended for ground contact applications, offers enhanced penetration as well as a broader spectrum of protection against decay organisms, particularly certain copper tolerant brown rots.



#### WARRANTY DETAIL

James Jones range of **INC15ED** ground contact fence posts and landscaping sleepers, when used in accordance with the appropriate standards, have a 15 year performance warranty against failure of the timber from fungal decay or insect attack.

The warranty is for the cost of re-supply by James Jones, or the re-supply by James Jones (at our option), of a component that is proven to have failed as a result of fungal decay or insect attack within 15 years of supply.

The warranty does not cover the costs of removal or reinstatement of such components or consequential costs or loss due to failure of the component. Claims must be brought within two weeks of the expiry of the 15 year period, at the latest.

The term 'fungal decay' as used in the warranty refers to wood destroying fungi that feed on and degenerate the wood cell walls. It excludes staining and mould fungi associated with the weathering of wood.

The term 'insect attack' refers to attack by wood digesting insects that destroy the timber structure.

The term 'failed' refers to damage caused by insects and/or fungi to such an extent that the component is no longer fit for purpose.

#### WARRANTY CONDITIONS

Just like any other product we use in everyday life James Jones range of **INC15ED** ground contact fence posts and landscaping sleepers have to be used correctly to ensure they perform correctly.

1. The James Jones range of **INC15ED** ground contact fence posts and landscaping sleepers must not have been misused or placed in abnormal conditions and must not have been used for any extraordinary purpose which was not drawn to the attention of James Jones or the retailer at the time of purchase.

2. Should James Jones range of **INC15ED** ground contact fence posts and landscaping sleepers be cross cut, notched or bored during installation, then exposed surfaces must be liberally brushed with a suitable brush-on end grain wood preservative to the directions shown on the product label, to protect the integrity of the treatment.

3. James Jones range of **INC15ED** ground contact fence posts and landscaping sleepers must not be pointed after treatment.

4. The shortening of James Jones range of **INC15ED** ground contact fence posts and landscaping sleepers should be avoided, if possible. If unavoidable the cut end must be treated with a suitable end grain wood preservative and must never be used in ground contact.

5. James Jones range of **INC15ED** ground contact fence posts and landscaping sleepers must not be planed or ripped.
6. The warranty covers proven failure by the preservative system only and James Jones reserve the right to allow Arch or Wolman to investigate any claims to ensure that they are relevant.

7. Any claim must be accompanied by proof of purchase.

#### Exclusions

1. Components used outside of European markets.
2. Components removed from their original installation and re-used at a new location.
3. Failure due to physical damage as a result of mechanical strimming, or other external forces.
4. Claims for weathering of wood including: ageing, raised grain, splitting, cracking, warping, shrinkage, swelling.
5. Claims for natural movement of wood in service, including weathering, twisting and splitting;
6. Claims for mould growth.

#### STOCKIST

Insist on  
**INC15ED**  
years

High Performance  
Posts and Sleepers  
Guaranteed for 15 Years



The INC15ED range of preservative treated posts and landscaping sleepers from James Jones gives added confidence to your next fencing or landscaping project.

Manufactured from quality whitewood, our posts and sleepers are kiln dried and **INC15ED** prior to preservative treatment to Use Class 4 ground contact requirements.

Consistent and uniform incisions enable a minimum of 6mm preservative treatment penetration to meet Use Class 4 (EN335) and BS8417 ground contact requirements.

This allows James Jones & Sons to offer a **15 year warranty** against rot and insect attack on our **INC15ED** range of fencing and landscaping timbers.



**James Jones  
& SONS LIMITED**

# Product Range



## INC15ED FENCE POSTS

The following core range of INC15ED fence posts is available either green or brown pressure treated.

WIDTH/DEPTH	LENGTHS
75mm x 75mm	1.5m, 1.8m, 2.1m, 2.4m, 2.7m, 3.0m
75mm x 100mm	2.4m
100mm x 100mm	1.8m, 2.4m, 3.0m

(Other specifications are available on request.)

The James Jones **INC15ED** product range complements our extensive choice of quality fencing products available.

• **RAILS** • **SLATS** • **RANCH & GRAVEL BOARDS** • **FEATHEREDGE BOARDS**

The entire James Jones fencing range is available either green or brown pressure treated.

## INC15ED SLEEPERS

**INC15ED** landscaping sleepers are available to order in the following sections.

WIDTH/DEPTH	LENGTHS
100mm x 200mm	2.4m

(Other specifications are available on request.)



## CUT & TREAT

Every time pressure preservative treated timber is cut or notched during installation, the exposed surfaces must be further protected with an appropriate brush-on end grain preservative to maintain the integrity of the performance and the conditions of the warranty.



**James Jones  
& SONS LIMITED**



**James Jones  
& SONS LIMITED**

